

HOOTER (Sounder)

Product Overview

Exclusive range of Fire Alarm Hooter (Sounder) with addressable & Conventional type with Red & White plastic Housings. The wall mounted medium frequency hooter designed as per NFPA-72 to complete the demand of Fire Alarm systems in several areas of residential, commercial & Industrial application. The Fire Alarm Hooter is a device that produce sound when Manual Call Point & Detector sense any kind of fire activity. It has dual tone sound and it is enough to make alert everyone inside the building.



AGNI-401

1. FEATURES	
Compatibility with Fire Alarm/other safety Control Panel	
Continually rated	
ABS Body	
2. TECHNICAL SPECIFICATIONS	
SYSTEM OPERATING VOLTAGE	24 VOLT DC
SOUND PRESSURE LEVEL	90dB at 25 Meter
TONE NATURE	Dual Tone
FREQUENCY RANGE	(500Hz-1000Hz)
OUTPUT	4 WATTS
SPEAKER	8O 4 WATTS
ALARM CURRENT	200mA-Peak
OPERATING TEMP.	10°C to 42°C
WEIGHT	350gm.
CABLE ENTRY	TOP / BACK 20MM KNOCKOUT
FIXING HOLE	2 No.
CABINET	(ABS-FR) Body
PROTECTION TYPE	IP65